

GAMMA INSTABUS UNIVERSAL DIMMER UP 525/31  
210W 2 BINARY INPUT



Similar to image

Technical data:

|   |   |                            |
|---|---|----------------------------|
| <b>Design type</b>                                    |   | lighting                   |
| <b>Type, explanations</b>                             |   | dimmer                     |
| <b>Type, explanations / additionally</b>              |   | universal dimmer UP 525/31 |
| <b>Design, description / additional supplementary</b> |   | 210 VA, 230 V AC, 50Hz     |
| <b>Design of the product</b>                          |   | dimming actuator           |
| <b>Type of mounting</b>                               |   | others                     |
| <b>Number of analog outputs</b>                       |   | 1                          |
| <b>Adjustable real power</b>                          | W | 50 ... 210                 |
| <b>Operating voltage</b>                              |   |                            |
| • rated value   | V | 230 ... 230                |
| <b>Product component</b>                              |   |                            |
| • integrated / Bus coupling                           |   | Yes                        |
| • Extension input                                     |   | Yes                        |
| • LED   |   | No                         |
| <b>Bus system / can be used / EIB/KNX</b>             |   | Yes                        |
| <b>Bus system / usable / RF bus system</b>            |   | No                         |
| <b>Bus system / usable / Powernet bus system</b>      |   | No                         |
| <b>Bus system / usable / LON bus system</b>           |   | No                         |

|   |    |               |
|---|----|---------------|
| <b>Product function</b>   |    |               |
| • Parallel operation  |    | No            |
| • direct operation  |    | No            |
| <b>Extension de produit / en option / puissance additionnelle</b>         |    | No            |
| <b>Operating frequency</b>  |    |               |
| • rated value   | Hz | 60 ... 50     |
| <b>Type of load</b>   |    | universal     |
| <b>Protection class IP</b>  |    | IP20          |
| <b>Design</b>   |    | flush-mounted |
| <b>Dimmer performance in W</b>  |    | 50 to 210     |
| <b>Electrical output protection against overload and short-circuiting</b> |    | yes           |
| <b>Load type</b>  |    | R,L,C         |
| <b>Integrated bus coupling unit</b>                                       |    | yes           |

#### Certificates/approvals:

General Product Approval

Declaration of Conformity



GOST



EG-Konf.

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/mall>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5WG1525-2AB31/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5WG1525-2AB31](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1525-2AB31)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

**last change:**

Jul 1, 2013