

GAMMA INSTABUS BINARY INPUT DEVICE N 263E/11 16
X 12...230V AC/DC,
6MW



Similar to image

Technical data:

Type of mounting		modular installation device
Number of digital inputs		16
Number of pitch units for width		6
Input voltage / minimum	V	12
Input voltage / maximum	V	230
Type of display / LED		Yes
Bus system / can be used / EIB/KNX		Yes
Bus system / usable / RF bus system		No
Product component / integrated / Bus coupling		Yes
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Protection class IP		IP20
Product feature / LED control		No
Design type		binary input devices
Type, explanations		binary input device N 263E11
Type, explanations / additionally		16 inputs for 12 to 230 V AC, 12 to 115 V DC
Integrated bus coupling unit		yes
Dimensions width	mm	108

Certificates/approvals:

General Product Approval



Declaration of Conformity

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1263-1EB11/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1263-1EB11

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Mar 4, 2013