

SWITCHING ACTUATOR RL 512/23 1X 16AX,
AC 230V (RELAY) 1X 15A, AC277V / AC 347V



Similar to image

Technical data:		
Type of display / LED		No
Type of mounting		modular installation device
Switching capacity real power	W	3,680
Breaking capacity current	A	16
Bus system / can be used / EIB/KNX		Yes
Bus system / usable / RF bus system		No
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Number of switching outputs / maximum		1
Operating current / rated value	A	16
Operating voltage		
• rated value	V	230 ... 230
Product function / direct operation		No
Product component / integrated / Bus coupling		Yes
Protection class IP		IP20

Certificates/approvals:

Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1512-4AB23/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1512-4AB23

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Sep 2, 2013