


VR170, ZN170, Z171T

Float valve for water storage tanks
with option of stainless steel or plastics floats

Product specification sheet



Application

Float valves of this type regulate a fluid level in vented open or closed storage vessels or can be used for filling of water supply storage tanks. Within the scope of their specification they can be used for industrial or commercial installations or also for public water supply systems. A soft seat seal provides positive shutoff, even with fluctuating supply pressure.

Special Features

- Available with plastics or stainless steel floats
- Float can be fitted horizontally or vertically
- Open construction design
- External thread connection to DIN 228
- High flow capacity
- Seat seal and piston replaceable
- Lever arm can be shortened where supply pressure is low

Range of Application

Medium	Water and neutral liquids
Installation	Horizontally on water storage vesse

Technical Data

Max. operating temperature	65 °C with plastics float 90 °C with stainless steel float
Max. operating pressure	6.0 bar 8.0 bar with stainless steel float of next larger size
Connection size	R1½" - R2½"


Construction

The float valve comprises:

- Housing
- Piston
- Lever arm
- Float

Materials

- Brass housing (½" to 2") or red bronze (2½")
- Brass piston
- Brass lever arm (½" to 1") or stainless steel (1¼" to 2½")
- Plastics or stainless steel float
- NBR seals

**Float valve VR170**

Connection size	R	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"
Outlet	R1	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Total weight	kg	1.0	1.1	1.3	2.0	2.6	3.8	5.3
Dimensions	(mm)							
Ø D _o		9	12	15	20	25	30	35
L		600	610	720	730	890	900	1150
A		120	130	135	180	315	325	430
B		90	100	110	130	150	165	185
C		30	30	37	44	50	55	62
I ₁		30	35	38	45	50	50	55
I ₂		54	54	54	66	66	78	78
Lever arm	BxTxL	15x6x570	15x6x570	15x6x680	20x6x680	20x6x825	20x6x825	20x8x1060
k _{vs} -value	m ³ /h	2	3.6	5.5	9.4	13	17.5	21

Stainless steel float ZN170

Connection size	R	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
Weight	kg	0.4	0.5	0.7	0.8	1.0	1.2	1.2	1.4
Dimensions	(mm)								
Ø D _o		153	153	183	183	233	233	310	330
H		163	178	188	225	225	268	245	245
h		125	140	150	180	180	220	200	200
Lift	approx. kg	1.5	1.7	2.8	3.5	5.0	6.5	8.5	11.5

Plastics float Z171T

Connection size	R	For 1/2" 3/4" 1" float valves	For 1 1/4" 1 1/2"** 2*** float valves
Weight	kg	0.2	0.4
Dimensions	(mm)		
D _o		130	200
H		248	278
h		130	160
Lift	approx. kg	1.2	3.5

* Valve connection 1 1/2" to 5 bar and

** Valve connection 2" to 3 bar operating pressures

Automation and Control Solutions

Honeywell GmbH
 Hardhofweg
 D-74821 Mosbach
 Phone: (49) 6261 810
 Fax: (49) 6261 81309
<http://europe.hbc.honeywell.com>
www.honeywell.com

Manufactured for and on behalf of the
 Environmental and Combustion Controls Division
 of Honeywell Technologies Sàrl, Ecublens, Route
 du Bois 37, Switzerland by its Authorised Representative Honeywell GmbH

ENOH-1322GE23 R0807
 Subject to change without notice
 © 2007 Honeywell GmbH

Honeywell